



CNWPVC-10

MAY, 2007

PLEASE ORDER BY PART NUMBER.

10' BELLED END PVC SCH 40 RIGID ELECTRICAL CONDUIT	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PERCENT OF TL	MIN. BELL LENGTH	PART NO.
 ELECTRICAL UL 651	½"	.840	.622	.109	16.12	3000	0.9	1.750	58015
	¾	1.050	.824	.113	21.50	4400	2.1	2.000	58025
	1	1.315	1.049	.133	31.89	3600	1.7	2.250	58035
	1¼	1.660	1.380	.140	43.24	3300	2.6	2.500	58045
	1½	1.900	1.610	.145	51.65	2250	2.5	2.750	58055
	2	2.375	2.067	.154	69.85	1400	2.1	3.250	58065
	2½	2.875	2.469	.203	110.80	930	2.3	3.500	58075
	3	3.500	3.068	.216	145.13	880	2.9	4.000	58085
	4	4.500	4.026	.237	206.63	570	3.0	4.750	58095
	6	6.625	6.065	.280	363.36	260	3.6	6.375	58105

20' BELLED END PVC SCH 40 RIGID ELECTRICAL CONDUIT  ELECTRICAL UL 651	¾	1.050	.824	.113	21.50	8800	4.0	2.000	58020
	1	1.315	1.049	.133	31.89	7200	5.0	2.250	58030
	1¼	1.660	1.380	.140	43.24	6600	5.3	2.500	58040
	1½	1.900	1.610	.145	51.65	4500	3.6	2.750	58050
	2	2.375	2.067	.154	69.85	2800	4.2	3.250	58060
	2½	2.875	2.469	.203	110.80	1860	4.6	3.500	58070
	3	3.500	3.068	.216	145.13	1760	5.8	4.000	58080
	4	4.500	4.026	.237	206.63	1140	6.0	4.750	58090
	6	6.625	6.065	.280	363.36	520	7.2	6.375	58100

PVC SCH 40 ELECTRICAL CONDUIT IS GRAY IN COLOR.

PVC SCH 40 ELECTRICAL CONDUIT CONFORMS TO: UL 651 INCLUDING 90° C RATING
NEMA TC 2
SUNLIGHT RESISTANT

CRESLINE-NORTHWEST, LLC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD · EVANSVILLE, IN 47715 · TELEPHONE (812) 428-9300

PLANT: 223 MAURIN ROAD · CHEHALIS, WA 98532 · TELEPHONE (360) 740-0708 · FAX (360) 740-0721