


CRESLINE-WEST®


PVC THREADED DROP PIPE

CWPVC-8

APRIL, 2010

PLEASE ORDER BY PART NUMBER


PVC SCH-80 THREADED DROP PIPE ASTM D-1785 	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	MAX PSI 73°F	FEET PER PALLET	PALLETS PER TL	PART NO.
	1"	1.315	.957	.179	41.23	315	2600	44	43056
	1¼"	1.660	1.278	.191	57.18	260	2000	44	43078
	1½"	1.900	1.500	.200	69.19	235	2360	40	43085
	2"	2.375	1.939	.218	95.89	200	1860	32	43100

PVC SCH-120 THREADED DROP PIPE ASTM D-1785 	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	MAX PSI 73°F	FEET PER PALLET	PALLETS PER TL	PART NO.
	1"	1.315	.915	.200	45.21	360	2600	44	43350
	1¼"	1.660	1.230	.215	63.12	300	2000	44	43370
	1½"	1.900	1.450	.225	76.61	270	2360	40	43380
	2"	2.375	1.875	.250	108.10	240	1860	32	43390

STANDARD LENGTH 20 FT. PROTECTIVE END CAPS PLACED ON ALL THREADED PIPE.

ALL SCH-80 THREADED DROP PIPE IS CERTIFIED TO THE UNIFORM PLUMBING CODE BY NSF INTERNATIONAL.

ALL SCH-80 AND SCH-120 THREADED DROP PIPE IS CERTIFIED TO NSF/ANSI 61, ANNEX G (CA AND VT LEAD FREE LAWS) BY NSF INTERNATIONAL.

WW25 MACHINED COUPLING			
	SIZE	PART NO.	QTY.
	1"	85250	10/100
	1¼"	85252	10/100
	1½"	85253	10
	2"	85254	10
THREAD X THREAD EXTRA HEAVY - SCH 120 FOR USE ON THREADED DROP PIPE			

CRESLINE - WEST, INC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD · EVANSVILLE, IN 47715 · TELEPHONE (812) 428-9300

PLANT: 3747 W. BUCKEYE ROAD · PHOENIX, AZ 85009 · TELEPHONE (602) 269-5161

WAREHOUSE: 1930 W. WHITESBRIDGE ROAD · FRESNO, CA 93706 · TELEPHONE (559) 486-1840

www.cresline.com

PVC THREADED DROP PIPE DEPTH GUIDELINES

PVC THREADED SCHEDULE 80 PIPE HORSEPOWER RATINGS - DEPTH CHART						
SIZE	MAX HP	RECOMMENDED FITTINGS	PUMPING LIMITATIONS - BASED ON SHUT-OFF SWITCH			TORQUE ARRESTOR
			40 PSI	50 PSI	60 PSI	
1"	1.5	EXTRUDED COUPLINGS	610'	590'	570'	USE OVER 150'
1 1/4"	2	EXTRUDED COUPLINGS	475'	455'	435'	USE OVER 150'
1 1/2"	5	STEEL OR BRASS COUPLINGS	435'	415'	395'	USE OVER 150'
2"	7.5	STEEL OR BRASS COUPLINGS	350'	325'	300'	USE OVER 150'

PVC THREADED SCHEDULE 120 PIPE HORSEPOWER RATINGS - DEPTH CHART						
SIZE	MAX HP	RECOMMENDED FITTINGS	PUMPING LIMITATIONS - BASED ON SHUT-OFF SWITCH			TORQUE ARRESTOR
			40 PSI	50 PSI	60 PSI	
1"	1.5	EXTRUDED COUPLINGS	700'	675'	650'	USE OVER 150'
1 1/4"	2	EXTRUDED COUPLINGS	570'	545'	520'	USE OVER 150'
1 1/2"	5	STEEL OR BRASS COUPLINGS	531'	508'	485'	USE OVER 150'
2"	7.5	STEEL OR BRASS COUPLINGS	435'	415'	395'	USE OVER 150'

NSF[®] pw-G U.P.Code



CRESLINE - WEST, INC.
CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD · EVANSVILLE, IN 47715 · TELEPHONE (812) 428-9300
PLANT: 3747 W. BUCKEYE ROAD · PHOENIX, AZ 85009 · TELEPHONE (602) 269-5161
WAREHOUSE: 1930 W. WHITESBRIDGE ROAD · FRESNO, CA 93706 · TELEPHONE (559) 486-1840
www.cresline.com