



CWPVC-5


SEPTEMBER, 2020

PLEASE ORDER BY PART NUMBER.

PVC-DWV SCH-40  ASTM D2665    ASTM D1785  	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PALLETS PER T.L.	PART NO.
	1½"	1.900	1.610	.145	51.83	5180	20	50215
	2	2.375	2.067	.154	69.71	3340	20	50225
	3	3.500	3.068	.216	144.82	1500	20	50235
	4	4.500	4.026	.237	206.19	960	20	50245
	6	6.625	6.065	.280	363.36	400	20	50255
	8	8.625	7.981	.322	546.91	280	16	50265
	10	10.750	10.020	.365	775.36	160	16	42155
	12	12.750	11.938	.406	1025.36	120	12	42165

1 1/2" - 8" PVC-DWV SCH-40 PIPE IS CERTIFIED TO THE UNIFORM PLUMBING CODE BY NSF INTERNATIONAL.

ALL PVC-DWV SCH-40 PIPE IS CERTIFIED TO NSF/ANSI 61, ANNEX G (CA AND VT LEAD FREE LAWS) BY NSF INTERNATIONAL.

PVC-DWV CELLULAR CORE  ASTM F891  	1½"	1.900	1.610	.145	37.90	5180	20	51115
	2	2.375	2.067	.154	47.46	3340	20	51125
	3	3.500	3.068	.216	94.25	1500	20	51135
	4	4.500	4.026	.237	134.17	960	20	51145
	6	6.625	6.065	.280	236.39	400	20	51155
	8	8.625	7.981	.322	355.81	280	16	51165

PVC-DWV CELLULAR CORE PIPE IS NOT FOR USE IN PRESSURE SYSTEMS.

1 1/2" - 8" PVC-DWV CELLULAR CORE PIPE IS CERTIFIED TO THE UNIFORM PLUMBING CODE BY NSF INTERNATIONAL.

CRESLINE-WEST PVC-DWV PIPE IS FURNISHED IN WHITE PLAIN END LENGTHS AND NOT RECOMMENDED FOR THREADING.

NSF® dwv U.P. Code

NSF® pw-G U.P. Code

CRESLINE - WEST, INC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD · EVANSVILLE, IN 47715 · TELEPHONE (812) 428-9300

PLANT: 3747 W. BUCKEYE ROAD · PHOENIX, AZ 85009 · TELEPHONE (602) 269-5161

www.cresline.com