



CWPVC-8

SEPTEMBER, 2020

PLEASE ORDER BY PART NUMBER

PVC SCH-80 THREADED DROP PIPE ASTM D1785 	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	MAX PSI 73°F	FEET PER PALLET	PALLETS PER TL	PART NO.
	1"	1.315	.957	.179	41.23	315	2600	44	43056
	1¼	1.660	1.278	.191	57.18	260	2000	44	43078
	1½	1.900	1.500	.200	69.19	235	2360	40	43085
	2	2.375	1.939	.218	95.89	200	1860	32	43100

PVC SCH-120 THREADED DROP PIPE ASTM D1785 	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	MAX PSI 73°F	FEET PER PALLET	PALLETS PER TL	PART NO.
	1"	1.315	.915	.200	45.21	360	2600	44	43350
	1¼	1.660	1.230	.215	63.12	300	2000	44	43370
	1½	1.900	1.450	.225	76.61	270	2360	40	43380
	2	2.375	1.875	.250	108.10	240	1860	32	43390

STANDARD LENGTH 20 FT. PROTECTIVE END CAPS PLACED ON ALL THREADED PIPE.

ALL SCH-80 THREADED DROP PIPE IS CERTIFIED TO THE UNIFORM PLUMBING CODE BY NSF INTERNATIONAL.

ALL SCH-80 AND SCH-120 THREADED DROP PIPE IS CERTIFIED TO NSF/ANSI 61, ANNEX G (CA AND VT LEAD FREE LAWS) BY NSF INTERNATIONAL.

CRESLINE - WEST, INC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD • EVANSVILLE, IN 47715 • TELEPHONE (812) 428-9300

PLANT: 3747 W. BUCKEYE ROAD • PHOENIX, AZ 85009 • TELEPHONE (602) 269-5161

www.cresline.com

PVC THREADED DROP PIPE DEPTH GUIDELINES

PVC THREADED SCHEDULE 80 PIPE HORSEPOWER RATINGS - DEPTH CHART						
SIZE	MAX HP	RECOMMENDED FITTINGS	PUMPING LIMITATIONS - BASED ON SHUT-OFF SWITCH			TORQUE ARRESTOR
			40 PSI	50 PSI	60 PSI	
1"	1.5	EXTRUDED COUPLINGS	610'	590'	570'	USE OVER 150'
1 1/4"	2	EXTRUDED COUPLINGS	475'	455'	435'	USE OVER 150'
1 1/2"	5	STEEL OR BRASS COUPLINGS	435'	415'	395'	USE OVER 150'
2"	7.5	STEEL OR BRASS COUPLINGS	350'	325'	300'	USE OVER 150'

PVC THREADED SCHEDULE 120 PIPE HORSEPOWER RATINGS - DEPTH CHART						
SIZE	MAX HP	RECOMMENDED FITTINGS	PUMPING LIMITATIONS - BASED ON SHUT-OFF SWITCH			TORQUE ARRESTOR
			40 PSI	50 PSI	60 PSI	
1"	1.5	EXTRUDED COUPLINGS	700'	675'	650'	USE OVER 150'
1 1/4"	2	EXTRUDED COUPLINGS	570'	545'	520'	USE OVER 150'
1 1/2"	5	STEEL OR BRASS COUPLINGS	500'	480'	455'	USE OVER 150'
2"	7.5	STEEL OR BRASS COUPLINGS	435'	415'	395'	USE OVER 150'

NSF® pw-G U.P. Code

